



**Standards:**

- EN60598-1:2008,
- EN60598-2-1:1989,
- EN61347-1:2007,
- EN61347-2-13:2006,
- EN55015:2006.
- EN61547:2009.
- EN61000-3-2:2006.
- EN61000-3-3:2008

**Features:**

- Wall-mount / Ceiling Mount.
- Grand style with long lifetime (up to 50,000hrs).
- Energy saving - over 85% efficiency and power factor.
- Low heat dissipation.

**Specification:**

- Optional with self-contained, maintained type, automatic changeover device for minimum 2 or 3 hours battery back up.

<b>Model</b>	<b>ALS-ETLR-CEILING</b>
<b>Power</b>	7W / 9W / 11W / 13W / 15W
<b>Lumen</b>	450lm(7W) / 550lm(9W) / 650lm(11W) 750lm(13W) / 850lm(15W)
<b>Size</b>	Dia 320 x H 100 (mm) <small>***Adjustable</small>
<b>Beam Angle</b>	120°
<b>Color Temp</b>	3000K / 4000K / 5600K
<b>Voltage</b>	A/C 220V 50Hz +/-5%
<b>Power Factor</b>	>0.85
<b>Style</b>	Grand
<b>Battery Type</b>	Model: ALS-ETLR-CEILING-B

\*\*\*2 to 3 hours discharge available