



**Standards:**

- EN60598-2-22:2008,
- BS 5266 Part 1:2005,
- BS EN 60598-2-22:2002,
- FSD PPA 104(A) 4<sup>th</sup> Revision.

**Features:**

- Wall-mount / Ceiling Mount.
- Grand style with I.P. 65 Index.
- Lamp Source: 2D fluorescent.
- Red LED to indicate mains supply and healthy charging status.
- Test Button to allow easy checking of luminaries operation.

**Specification:**

- Maintained / Non-maintained type, Self-contained, automatic changeover device for minimum 2 or 3 hours battery back up.

Model	ALS-2C-2D28	ALS-2C-2D38
Power	2D 28W	2D 38W
Battery Type	Sealed Ni-Cad <small>***Sealed Ni-Mh are available</small>	
Mode of Operation	Maintained Type <small>***Non-maintained type are available</small>	
Emergency Output	0.25 BLF <small>***Adjustable</small>	
Emergency Duration	2 Hours <small>***3 Hours are available</small>	
Battery	9.6v 2.2mAh	9.6v 2.5mAh
Size	315L x 315D x 95H (mm)	
Voltage	A/C 220V 50Hz +/-5%	
Index of Protection	I.P.65	
Recharge Period	12 Hours for 2 Hours Discharge <small>***2 to 3 hours discharge available</small>	