



**Standards:**

- BS 5266 Part 1:2005,
- BS EN 60598-2-22:2002,
- FSD PPA 104(A) 4<sup>th</sup> Revision.

**Features:**

- Suitable for all compact fluorescent lamp.
- Metal housing constructed of galvanized steel with EPOXY powder coating.
- For long extended services life and highly reliability quality components.
- Red and Green LED to indicate mains supply and charge are functioning.
- Test Button to allow easy checking of luminaries operation.

**Specification:**

- Maintained / Non-maintained type, Self-contained, automatic changeover device for minimum 2 or 3 hours battery back up.

Model	ALS-2C-C18	ALS-2C-C26	ALS-2C-C32
Suitable to	PL/PLC: 7-18W <small>*4Pins</small>	PL/2D: 26-32W <small>*4Pins</small>	PL/PLC/2D: 7-28W <small>*2Pins</small>
Battery Type	Sealed Ni-Cad <small>***Sealed Ni-Mh are available</small>		
Mode of Operation	Maintained Type <small>***Non-maintained type are available</small>		
Emergency Output	0.25 BLF <small>***Adjustable</small>		
Emergency Duration	2 Hours <small>***3 Hours are available</small>		
Battery	6V 2.2Ah	6V 2.2Ah	12V 2.5Ah
Line Voltage	A/C 220V 50Hz +/-10%		
Recharge Period	12 Hours for 2 Hours Discharge		
Metal Box Size (mm)	330L x 100H x 60D <small>***Options will be available upon request</small>		