



**Standards:**

- BS 5266 Part 1:2005,
- BS EN 60598-2-22:2002,
- FSD PPA 104(A) 4<sup>th</sup> Revision.

**Features:**

- Suitable for MR16 12V 25W/50W/75W/100W Tungsten Halogen.
- Slim size remote metal box with white powder coated.
- For long extended services life and highly reliability quality components.
- Red and Green LED to indicate mains supply and charge are functioning.
- Test Button to allow easy checking of luminaries operation.

**Specification:**

- Remote metal box, self-contained, non-maintained type, emergency battery pack with automatic changeover device for minimum 2 or 3 hours battery back up.

<b>Model</b>	<b>ALS-1250-2</b>
<b>Battery Type</b>	Sealed Lead Acid <small>***Sealed Ni-Cd/Ni-Mh are available</small>
<b>Mode of Operation</b>	Maintained Type <small>***Non-Maintain type are available</small>
<b>Emergency Output</b>	Minimum 50% <small>***Adjustable</small>
<b>Emergency Duration</b>	2 Hours <small>***3 Hours are available</small>
<b>Battery</b>	12V 8.0 Ah
<b>Line Voltage</b>	A/C 220V 50Hz +/-10%
<b>Recharge Period</b>	12 Hours for 2 Hours Discharge <small>***Option will be available upon request</small>