



Standards:

- BS 5266 Part 1:2005,
- BS EN 60598-2-22:2002,
- FSD PPA 104(A) 4th Revision.

Features:

- Suitable operate with 3 - 9W MR16 LED Spot Lamp.
- Operate with wide DC driver.
- Slim size remote metal box with white powder coated.
- Low voltage cutout and variable rate charger inverter to keep the battery long life.
- Test Button to allow easy checking of luminaries operation
- Red and Green LED to indicate mains supply and charge are functioning.

Specification:

- Remote metal box, self-contained, non-maintained type, emergency battery pack with automatic changeover device for minimum 2 or 3 hours battery back up.

Model	ALS-LED-5-2F
Battery Type	Sealed Ni-Cad <small>***Sealed Ni-Mh are available</small>
Mode of Operation	Maintained Type <small>***Non-Maintain type are available</small>
Emergency Output	Minimum 90% <small>***2 x 3W are available</small>
Emergency Duration	2 Hours <small>***3 Hours are available</small>
Battery	9.6V 2.0 Ah
Line Voltage	A/C 220V 50Hz +/-10%
Remote Box Size (mm)	240L x 140H x 50D
Recharge Period	12 Hours for 2 Hours Discharge <small>***Option will be available upon request</small>